

### **IN THE CLAIMS:**

Claim 12 is amended herein. All pending claims are produced below. In addition, the status of each is also indicated below.

1. (Previously presented) An electronic device, comprising:

a radio unit configured to communicate with a network;

at least one memory device configured to store programs; and

a processing unit coupled to said radio unit and said at least one memory device, said processing unit configured to run the programs;

wherein at least one of the programs comprises a notification program configured to display a software enabled switch for enabling the radio unit from a disabled state in response to a program attempting to utilize the radio unit while leaving the processing unit in an operation state, and further configured to display information for a context associated with a state of the software enabled switch.

2. (Previously Presented) An electronic device comprising:

a radio unit configured to communicate with a network;

at least one memory device configured to store programs; and

a processing unit couples to said radio unit and said at least one memory device, said processing unit configured to run the programs;

wherein:

at least one of the programs includes a software enabled switch for enabling and disabling the radio unit;

at least one of said programs is a program that utilizes the radio unit; and

at least one of said programs comprises a notification program configured to notify a user that the radio unit is disabled when invoking a program that is configured to utilize the radio unit and to display a software enabled switch, the software enabled switch further configured to either enable the radio unit for use by the program configured to utilize the radio unit or maintain the radio unit as disabled.

3. (Cancelled)

4. (Previously presented) The electronic device according to Claim 1, further comprising:

a display screen, wherein

at least one of the programs is configured to generate a graphical user interface on the display screen, the graphical user interface having at least one soft button programmed to enable or disable the radio unit.

5. (Previously presented) The electronic device according to Claim 4, wherein the graphical user interface has a first soft button labeled “*RADIO ON*,” and a second soft button labeled “*RADIO OFF*,” a status of the radio unit being indicated by the corresponding soft button highlighted in one of bold, inverse video, flashing, or other indicators.

6. (Previously presented) The electronic device according to Claim 1, further comprising a hard button programmed to enable and disable the radio unit, wherein the hard button is a toggle switch that is activated by engaging the toggle switch for a predetermined length of time.

7. (Original) The electronic device according to Claim 6, wherein said hard button has at least one additional program invoked by pressing the hard button for a time period less than said predetermined length of time.

8. (Original) The electronic device according to Claim 6, wherein said predetermined length of time is approximately 1 second.

9. (Previously presented) The electronic device according to Claim 1, wherein said software enabled switch comprises:

a user interface with a drop down menu having user selectable options for Radio On, Radio Off, and Schedule, and

a program configured to implement an option selected by a user.

10. (Original) The electronic device according to Claim 1, wherein the programs include a scheduling application that provides user modifiable start and stop times that indicate when the radio unit is enabled and disabled.

11. (Previously presented) A notification mechanism for notifying a user of a status of an RF device in an RF capable device, wherein the RF capable device includes a processing unit for running applications and a user interface, the notification mechanism comprising:

a check mechanism configured to check an enablement status of the RF device;

a user interface mechanism configured to display a status of the RF device, a software enabled switch on a touch-sensitive screen, and information for a context associated with a program that is previously invoked that requires RF capabilities, providing the user with an option to continue with the program and automatically enable the RF device or discontinue the program without enabling the RF device; and

an RF alarm mechanism configured to identify the program, wherein upon identifying the program, the RF alarm mechanism invokes the check mechanism to check the enablement status of the RF device, and if the RF device is not enabled, invokes the user interface mechanism.

12. (Currently amended) A method of notifying a user of an RF enablement status of a device having RF capabilities, comprising ~~the steps of~~:

identifying an invocation of a mechanism requiring access to the RF capabilities;

determining the RF enablement status of the device;

if the RF enablement status of the device is in a disabled state:

notifying the user if the mechanism is to be granted access to the RF

capabilities by displaying a software enabled switch and displaying information for a context associated with a state of the software enabled switch, and

receiving a user input regarding whether access to the RF capabilities should be granted to the mechanism;

if the user input indicates the mechanism is to be granted access to the RF capabilities:

automatically enabling the RF capabilities, and

allowing the mechanism to access the RF capabilities; and

if the user input indicates the mechanism is not to be granted access to the RF capabilities:

shutting down the mechanism without enabling the RF capabilities.

13. (Previously presented) The electronic device of Claim 1, wherein

at least one of the programs includes a prompting mechanism configured to display a prompt to a user to determine if the radio unit is to be enabled before enabling the radio unit.

14. (Previously Presented) The electronic device according to Claim 13, wherein:

said programs comprise a notification mechanism to identify when the radio unit is enabled.

15. (Previously Presented) The electronic device according to Claim 14, wherein the notification mechanism comprises display of an airplane icon.

16. (Previously presented) The electronic device according to Claim 13, further comprising a shutdown device configured to maintain the radio unit in the disabled state, maintain the processing unit in an operational state, and shut down an application program that utilizes the radio unit upon a negative response to the prompt from the user.

17. (Previously presented) The electronic device according to Claim 1, wherein the information for a context associated with a state of the software enabled switch further comprises a status display indicating enablement of the radio unit, the status display comprising an airplane icon.

18. (Previously Presented) The electronic device according to Claim 2, further comprising a status display indicating enablement of the radio unit, wherein the status display comprises an airplane icon.

19. (Previously Presented) The notification mechanism according to Claim 11, further comprising a display indicating enablement status of the radio unit, wherein the display comprises an airplane icon.

20. (Currently Amended) The method according to Claim 12, further comprising the step of displaying the enablement status of the RF device using an icon that comprises an airplane.

21. (Previously presented) The electronic device according to Claim 2, further comprising:

a display screen, wherein at least one of the programs is configured to generate a graphical user interface, the graphical user interface having a first soft button labeled “*RADIO ON*,” and a second soft button labeled “*RADIO OFF*,” a status of the radio unit being indicated by the corresponding soft button highlighted in one of bold, inverse video, flashing, or other indicators.

22. (Previously presented) The electronic device according to Claim 2, further comprising a hard button programmed to enable and disable the radio unit, wherein the hard button is a toggle switch that is activated by engaging the toggle switch for a predetermined length of time.

23. (Previously presented) The electronic device according to Claim 22, wherein the hard button has at least one additional program invoked by pressing the hard button for a time period less than the predetermined length of time.

24. (Previously presented) The electronic device according to Claim 22, wherein the predetermined length of time is approximately 1 second.

25. (Previously presented) The electronic device according to Claim 2, wherein the electronic device comprises a mobile phone.

26. (Previously presented) The electronic device according to Claim 25, wherein the mobile phone comprises a touch sensitive screen, the software enabled switch being displayed on the touch sensitive screen and being selectable.